

# 型钢捆重与包装规则

品种	类别	型号	成品截面尺寸						理论重量 kg/m	每捆 支数	12m定尺 捆重	包装规则	
			高度	宽度	腰厚	腿厚	R	bi			kg	打底	层数
H 型 钢	HN	500x200	496	199	9	14	13	468	77.9	5	4674	1	5
			500	200	10	16	13	468	88.1	5	5286	1	5
			506	201	11	19	13	468	102	5	6120	1	5
	HN	450x200	446	199	8	12	13	422	65.1	5	3906	1	5
			450	200	9	14	13	422	74.9	5	4494	1	5
	HW	400x300	390	300	10	16	13	358	105.0	6	7560	2	3
	HN	400x200	396	199	7	11	13	374	56.1	10	6732	2	5
			400	200	8	13	13	374	65.4	10	7848	2	5
	HM	350x250	340	250	9	14	13	312	78.1	6	5623	2	3
	HN	350x175	350	175	7	11	13	328	49.4	12	7114	2	6
			346	174	6	9	13	328	41.2	12	5933	2	6
	HW	300x300	294	302	12	12	13	270	83.5	6	6012	2	3
			300	300	10	15	13	270	93.0	6	6696	2	3
			300	305	15	15	13	270	105.0	6	7560	2	3
	HM	300x200	294	200	8	12	13	270	55.8	10	6696	2	5
	HN	300x150	298	149	5.5	8	13	282	32.0	14	5376	2	7
			300	150	6.5	9	13	282	36.7	14	6166	2	7
	HW	250x250	244	252	11	11	13	222	63.8	9	6890	3	3
			250	250	9	14	13	222	71.8	9	7754	3	3
			250	255	14	14	13	222	81.6	9	8813	3	3
	HM	250x175	244	175	7	11	13	222	43.6	15	7848	3	5
	HN	250x125	248	124	5	8	8	232	25.1	21	6325	3	7
			250	125	6	9	8	232	29.0	21	7308	3	7
	HW	200x200	200	200	8	12	13	176	49.9	16	9581	4	4
			200	204	12	12	13	176	56.2	16	10790	4	4
	HM	200x150	194	150	6	9	8	176	29.9	21	7535	3	7
	HN	200x100	198	99	4.5	7	8	184	17.8	40	8544	4	10
			200	100	5.5	8	8	184	20.9	40	10032	4	10
	HW	175x175	175	175	7.5	11	13	153	40.4	20	9696	4	5
	HW	150x150	150	150	7	10	8	130	31.1	24	8957	4	6

品种	型号	成品截面尺寸					理论重量 kg/m	每捆 支数	12m定尺 捆重	包装规则	
		高度	宽度	腰厚	腿厚	R			kg	打底	层数
槽 钢	16a	160	63	6.5	10	10	17.2	56	11558	4	14
	16b	160	65	8.5	10	10	19.8	56	13306	4	14
	18a	180	68	7	10.5	10.5	20.2	48	11635	4	12
	18b	180	70	9	10.5	10.5	23.0	48	13248	4	12
	20a	200	73	7	11	11	22.6	48	13018	4	12
	20b	200	75	9	11	11	25.8	48	14861	4	12
	22a	220	77	7	11.5	11.5	25.0	36	10800	3	12
	22b	220	79	9	11.5	11.5	28.5	36	12312	3	12
	25a	250	78	7	12	12	27.4	30	9864	3	10
	25b	250	80	9	12	12	31.3	30	11268	3	10
	25c	250	82	11	12	12	35.3	30	12708	3	10
	28a	280	82	7.5	12.5	12.5	31.4	20	7536	2	10
	28b	280	84	9.5	12.5	12.5	35.8	20	8592	2	10
	28c	280	86	11.5	12.5	12.5	40.2	20	9648	2	10
	30a	300	85	7.5	13.5	13.5	34.5	20	8280	2	10
	30b	300	87	9.5	13.5	13.5	39.2	20	9408	2	10
	30c	300	89	11.5	13.5	13.5	43.9	20	10536	2	10
	32a	320	88	8.0	14	14	38.1	20	9144	2	10
	32b	320	90	10.0	14	14	43.1	20	10344	2	10
	32c	320	92	12.0	14	14	48.1	20	11544	2	10
	36a	360	96	9	16	16	47.8	16	9178	2	8
	36b	360	98	11	16	16	53.5	16	10272	2	8
	36c	360	100	13	16	16	59.1	16	11347	2	8
	40a	400	100	10.5	18	18	58.9	16	11309	2	8
	40b	400	102	12.5	18	18	65.2	16	12518	2	8
	40c	400	104	14.5	18	18	71.5	16	13728	2	8

品种	型号	成品截面尺寸			理论重量 kg/m	每捆 支数	12m定尺 捆重	包装规则	
		边宽	边厚	R			kg	打底	包装方式
等 边 角 钢	14	140	10	14	21.5	58	14964	3	(3+2) X11+3
			12		25.5	48	14688	3	(3+2) X9+3
			14		29.5	38	13452	3	(3+2) X7+3
			16		33.4	33	13226	3	(3+2) X6+3
	16	160	10	16	24.7	48	14227	3	(3+2) X9+3
			12		29.4	38	13406	3	(3+2) X7+3
			14		34.0	33	13464	3	(3+2) X6+3
			16		38.5	28	12936	3	(3+2) X5+3
	18	180	12	16	33.2	35	13944	2	(2+1) X11+2
			14		38.4	32	14746	2	(2+1) X10+2
			16		43.5	26	13572	2	(2+1) X8+2
			18		48.6	23	13414	2	(2+1) X7+2
	20	200	14	18	42.9	29	14929	2	(2+1) X9+2
			16		48.7	23	13441	2	(2+1) X7+2
			18		54.4	20	13056	2	(2+1) X6+2
			20		60.1	20	14424	2	(2+1) X6+2
			24		71.2	17	14525	2	(2+1) X5+2
			25		74.0	14	12432	2	(2+1) X4+2

品种	型号	成品截面尺寸						理论重量 kg/m	每捆 支数	12m定尺 捆重	包装规则	
		高度	宽度	腰厚	腿厚	R	bi			kg	打底	层数
	16	160	88	6	9.9	8	133	20.5	50	12300	5	10
	18	180	94	6.5	10.7	8.5	151	24.1	40	11568	4	10
	20a	200	100	7	11.4	9	169	27.9	36	12053	4	9
	20b	200	102	9	11.4	9	169	31.1	36	13435	4	9
	22a	220	110	7.5	12.3	9.5	187	33.1	24	9533	3	8
	22b	220	112	9.5	12.3	9.5	187	36.5	24	10512	3	8
	25a	250	116	8	13	10	215	38.1	21	9601	3	7
	25b	250	118	10	13	10	215	42.0	21	10584	3	7
	28a	280	122	8.5	13.7	10.5	243	43.5	16	8352	2	8
	28b	280	124	10.5	13.7	10.5	243	47.9	16	9197	2	8
	30a	300	126	9	14.4	11	261	48.1	14	8081	2	7
	30b	300	128	11	14.4	11	261	52.8	14	8870	2	7
	30c	300	130	13	14.4	11	261	57.5	14	9660	2	7
	32a	320	130	9.5	15	11.5	280	52.7	14	8854	2	7

工 字 钢	32b	320	132	11. 5	15	11. 5	280	57. 7	14	9694	2	7
	32c	320	134	13. 5	15	11. 5	280	62. 7	14	10534	2	7
	36a	360	136	10	15. 8	12	318	60. 0	12	8640	2	6
	36b	360	138	12	15. 8	12	318	65. 7	12	9461	2	6
	36c	360	140	14	15. 8	12	318	71. 3	12	10267	2	6
	40a	400	142	10. 5	16. 5	12. 5	356	67. 6	12	9734	2	6
	40b	400	144	12. 5	16. 5	12. 5	356	73. 8	12	10627	2	6
	40c	400	146	14. 5	16. 5	12. 5	356	80. 1	12	11534	2	6
	45a	450	150	11. 5	18	13. 5	402	80. 4	6	5789	1	6
	45b	450	152	13. 5	18	13. 5	402	87. 4	6	6293	1	6
	45c	450	154	15. 5	18	13. 5	402	94. 5	6	6804	1	6
	50a	500	158	12	20	14	448	93. 6	6	6739	1	6
	50b	500	160	14	20	14	448	101	6	7272	1	6
	50c	500	162	16	20	14	448	109	6	7848	1	6
	55a	550	166	12. 5	21	14. 5	495	105	6	7560	1	6
	55b	550	168	14. 5	21	14. 5	495	114	6	8208	1	6
	55c	550	170	16. 5	21	14. 5	495	123	6	8856	1	6
	56a	560	166	12. 5	21	14. 5	505	106	6	7632	1	6
	56b	560	168	14. 5	21	14. 5	505	115	6	8280	1	6
	56c	560	170	16. 5	21	14. 5	505	124	6	8928	1	6

		26	76. 8	14	12902	2	(2+1) X4+2
		27	79. 5	14	13356	2	(2+1) X4+2

品种	型号	成品截面尺寸				理论重量	每捆支数	12m定尺捆重	包装规则	
		边宽	边宽	边厚	R	kg/m		kg	打底	包装方式
不等边角钢	16/10	160	10	10	13	19. 9	58	13850	3	(3+2) X11+3
				12		23. 6	48	13594	3	(3+2) X9+3
				14		27. 2	43	14035	3	(3+2) X8+3
				16		30. 8	38	14045	3	(3+2) X7+3
	18/11	180	110	10	14	22. 3	53	14183	3	(3+2) X10+3
				12		26. 5	43	13674	3	(3+2) X8+3
				14		30. 6	38	13954	3	(3+2) X7+3
				16		34. 6	33	13702	3	(3+2) X6+3
	20/12. 5	200	125	12	14	29. 8	38	13589	3	(3+2) X7+3
				14		34. 4	33	13622	3	(3+2) X6+3
				16		39. 0	28	13104	3	(3+2) X5+3
				18		43. 6	28	14650	3	(3+2) X5+3

此版与2020-8-8比较H250X125和H248X124每捆支数由24支改为21支，捆重相应变化。

2020-11-19